

Donner AutoFlow 02

Bezkontaktní hygienický provoz účinně zamezuje křížené kontaminaci.



EAN: 8596220009296

156,60 €

130,50 € bez DPH

The AutoFlow 02 automatic faucet is characterized by a unique design with sharply cut features.

Comfortable to use

Upon approaching your hand close to the sensor, the water flow will be automatically activated. The water temperature can be conveniently adjusted using the lever located on the right side. Once you move your hand away from the sensor, the water will stop within 1.5 seconds. The battery is equipped with an automatic water stop function after a few minutes, in case the sensor is permanently covered.

Water savings up to 60%.

The water flowing from the automatic faucet passes through a aerator, which aerates it and reduces its flow. Thanks to the fact that the water flows from the faucet only when you really need it. The combination of these two technologies brings water savings of 30-60 percent compared to a regular tap.

The Donner AutoFlow water tap releases water only when you need it. Additionally, it is equipped with an aerator that aerates the water and reduces its flow. As a result, the water consumption when using automatic faucets is 30-60 percent lower than when using regular faucets.

Sanitary operation.

Contactless operation effectively prevents cross-contamination. That is why these batteries are used in healthcare facilities, catering establishments, and other places with high hygiene requirements.

The supply hoses are equipped with an additional valve with a strainer to prevent backflow mixing of cold and hot water in the pipeline.

The ideal combination for maximum hygienic operation in toilets is a combination with hot air and jet dryer Jet Dryer.

Safe battery power.

The Donner AutoFlow 02 is powered by 4 AA batteries. The batteries are inserted into a case located under the sink. There is no need to worry about electrical outlet availability, and the risk of electric shock is completely eliminated. With the use of high-quality alkaline batteries and 200 activations per day, the battery life can last up to 1 year. In the event that the batteries are depleted, the water remains closed.

Power supply using an adapter

If you do not want to use battery power, the package includes a power adapter designed for a socket.

Quality materials

The body of the contactless battery AutoFlow 02 is made from one piece of brass. Its durable design makes it suitable for high-traffic operations. The battery surface is chrome-plated for easy maintenance.

Parts of the packaging:

- Assembly instructions
- Automatic battery
- 2x 50cm armored hose 1/2"
- 2x backflow valve with strainer 1/2"
- Battery adapter including holder
- Power adapter
- Bag with components (nut, sealing, washer, screw)

Parameters

Basic parameters

Model:	Donner AutoFlow 02
Warranty:	2 years
Product TARIC code:	84818090

Technical parameters

Material:	Brass-plated
Boot system:	Automatic infrared
Switching distance:	6-30 cm automatic calibration
Appropriate water temperature:	0-80 °C
Operating temperature:	0-45 °C
Armoured hoses:	2x 50cm 1/2" + 2x 1/2" check valve
Coarse dirt filter.:	Yes (sieve)

Electric specifications

Power:	Battery adapter 4x AA 1.5 V
--------	-----------------------------

Protective and security elements

Degree of protection:	IP56
Automatic water shut-off:	Yes

Dimensions, weight, packaging

Device dimensions:	190 x 150 x 56 mm (including handle 71 mm) (h/w/d)
Device weight:	1.3 kg
Packaging dimensions:	135 x 330 x 240 mm (w/l/h)
Weight including packaging (kg):	2 kg
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	26.5
Height of packaging (cm):	10.5
Depth of packaging (cm):	18.5



Model: AutoFlow 02

