# **Donner AutoFlow 03**

Bezkontaktní baterie zajistí vysoký hygienický standard na místech jako jsou nemocnice, zdravotnické zařízení, apod.



EAN: 8596220009302

152,52 €

127.10 € bez DPH

AutoFlow 03 is characterized by an elegant clean rounded design.

#### Simple to use.

The usage is very simple. After placing your hands in the sink, the water flow will start automatically. After finishing washing and moving your hands away from the sensor, the water flow will start automatically. You can adjust the water temperature using the mixing lever on the right side of the faucet. The faucet will automatically turn off the water flow after a few minutes of continuous operation.

### Water savings up to 60%.

In the head of the battery, there is a aerator that aerates the flowing water and effectively regulates its flow.

Thanks to the infrared sensor, the water flows only when you need it. Thanks to the aerator and the sensor, the water consumption is lower by 30-60 percent compared to a regular faucet.

#### Sanitary operation.

Completely touchless use prevents cross-contamination with bacteria and viruses. The operation is therefore very hygienic. Touchless faucets ensure a high hygiene standard in places such as hospitals, medical facilities, food establishments, and high-traffic areas. The supply hoses are equipped with an additional valve with a strainer to prevent backflow of cold and hot water in the pipes. The ideal complement to automatic faucets are touchless jet and hot air hand dryers Jet Dryer.

#### Safe battery power.

The Donner AutoFlow 03 faucet is powered by 4 AA batteries located in a compartment under the sink. This eliminates any issues with power cables. Additionally, the use is completely safe. In case the batteries run out, the faucet will remain closed. When using high-quality alkaline batteries, the battery life can last up to one year with 200 activations per day.

#### **Quality materials**

The body of the contactless battery AutoFlow 03 is made of brass. Its robust design guarantees long lifespan even in highly demanding conditions. The entire surface of the battery is chrome-plated for easy maintenance.

# Parts of the packaging:

- Assembly instructions
- Automatic battery
- 2x 50cm armored hose 1/2"
- 2x backflow valve with strainer 1/2"
- Battery adapter including holder
- Bag with components (nut, sealing, washer, screw)

## **Parameters**

#### **Basic parameters**

Model: Donner AutoFlow 03
Warranty: 2 years
Product TARIC code: 84818090

**Technical parameters** 

Material: Brass-plated
Boot system: Automatic infrared

Switching distance: 6-30 cm automatic calibration

Appropriate water temperature: 0-80 °C Operating temperature: 0-45 °C

Armoured hoses: 2x 50 cm 1/2" + 2x 1/2" check valve

Coarse dirt filter.: Yes (sieve)

**Electric specifications** 

Power: Battery adapter 4x AA 1.5 V

**Protective and security elements** 

Degree of protection: IP56
Automatic water shut-off: Yes

Dimensions, weight, packaging

Device dimensions:  $180 \times 190 \times 61 \text{ mm}$  (including handle 75 mm) (height/width/depth)

Device weight: 1.3 kg

Packaging dimensions:  $135 \times 330 \times 240 \text{ mm (w/l/h)}$ 

Weight including packaging (kg): 2 kg

Packing method: Protective polybag, polystyrene cover, cardboard box

Width of the packaging (cm): 26.5
Height of packaging (cm): 10.5
Depth of packaging (cm): 18.5





Model: AutoFlow 03













