

Donner AutoFlow 04

Baterie je vybavena čidlem, které rozpozná přítomnost rukou v umyvadle a samočinně spustí proud vody.



EAN: 8596220009319

144,48 €

120,40 € bez DPH

The automatic water faucet AutoFlow 04 has a functionalist design with a sharply cut top edge.

Easy to use

The battery is equipped with a sensor that detects the presence of hands in the sink and automatically turns on the water flow. The water temperature can be adjusted by a side lever mixer. The water flow automatically stops when hands are removed from the sink area. For safety reasons, the water will also stop after several minutes of continuous operation.

Water savings up to 60%.

AutoFlow automatic faucets save water twice. There is a aerator in the faucet head, which limits the water flow and aerates it. The sensor ensures that water flows only when you need it. By combining these technologies, water consumption is reduced by 30-60 percent.

Sanitary operation.

Contactless use prevents cross-contamination by bacteria and viruses. Automatic faucets are suitable for busy operations and facilities with high hygiene requirements, such as healthcare facilities and the like.

Inlet hoses are equipped with an additional valve with a screen to prevent backflow mixing of hot and cold water in the pipes. If you require maximum hygiene standards, perfect additions are contactless jet and hot air hand dryers Jet Dryer.

Safe battery power.

The Donner AutoFlow 04 touchless faucet is powered by four AA batteries. The batteries are located in a case under the sink. You don't have to worry about connecting a power cord. In case the batteries are drained, the water faucet will remain in a closed state. When using high-quality battery cells, it can operate for up to 1 year (200 activations/day).

Quality materials

The body of the battery is made of one piece of brass. The robust design is especially suitable for frequently visited bathrooms. The surface of the battery is chrome-plated for easy maintenance.

Parts of the packaging:

- Assembly instructions
- Automatic battery
- 2x 50cm armored hose 1/2"
- 2x backflow valve with strainer 1/2"
- Battery adapter including holder
- Bag with components (nut, sealing, washer, screw)

Parameters

Basic parameters

Model:	Donner AutoFlow 04
Warranty:	2 years
Product TARIC code:	84818090

Technical parameters

Material:	Brass-plated
Boot system:	Automatic infrared
Switching distance:	6-30 cm automatic calibration
Appropriate water temperature:	0-80 °C
Operating temperature:	0-45 °C
Armoured hoses:	2x 50cm 1/2" + 2x 1/2" check valve
Coarse dirt filter.:	Yes (sieve)

Electric specifications

Power:	Battery adapter 4x AA 1.5 V
--------	-----------------------------

Protective and security elements

Degree of protection:	IP56
Automatic water shut-off:	Yes

Dimensions, weight, packaging

Device dimensions:	185 x 111 x 56 mm (including handle 71 mm) (l/w/h)
Device weight:	1.3 kg
Packaging dimensions:	135 x 330 x 240 mm (w/l/h)
Weight including packaging (kg):	2 kg
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	26.5
Height of packaging (cm):	10.5
Depth of packaging (cm):	18.5



Model: AutoFlow 04

