

EcoMaster II. JAKOST HEAVY DUTY Plus

VYSTAVENO/ROZBALENO - více informací v popisu



EAN: 8596220000033x

214,68 €

178,90 € bez DPH

II. quality

We offer 2 pieces of crushers in second quality. UNPACKED, may have slight scratches. Original packaging is damaged.

Food waste disposer is recommended for all households. It optimally combines all parameters and improvements typical for more luxurious models.

Compared to the cheaper STANDARD model, it has a larger and deeper grinding chamber, overall motor and chamber insulation, including insulation filling.

It also includes a waste bend with an inlet for potential connection of the sink overflow and an improved plug for filling the sink made of high-quality stainless steel with sealing, including a plastic longitudinal handle.

Surface treatment of the neck - polished matte stainless steel with the EcoMaster logo.

Welt Servis Ltd. holds products and spare parts in stock and provides warranty and post-warranty service and professional installations for households and catering establishments throughout the Czech Republic.

Parts of the packaging:

- Assembly instructions
- Removable rubber cuff
- Waste bend with additional inlet for overflow / dishwasher including flange and screws.
- Plug made of high-quality stainless steel with seal including a plastic handle.

Parameters

Basic parameters

| | |
|---------------------|------------------------------------|
| Model: | EcoMaster HEAVY DUTY Plus |
| Use: | Powerful model for demanding users |
| Warranty: | 4 years |
| Product TARIC code: | 85098000 |

Technical parameters

| | |
|---|---|
| Mounting method - installation: | Hanging under the sink |
| Sink flange clamping system: | EZ Mount |
| Sink flange material: | Plastic (Flanged Flange) |
| Housing material - case: | ABS plastic |
| Surface finish - color: | White lacquer finish |
| Boot system: | Pressure air switch, button |
| Size of the chamber: | L |
| Grinding segments: | Stainless steel, reinforced blades |
| Grinding ring: | 36 arch holes, projections |
| Bearings: | Bronze, self-lubricating |
| Protective cushion: | Removable splash guard |
| Sink drain hole: | Ø 9cm (3.5 ") |
| Maximum sink thickness: | 15 mm (at clamping point) |
| Dishwasher / washing machine connection, sink overflow: | Yes |
| Soundproofing: | Engine and grinding chamber cover + insulating filler |
| Average water consumption: | 10 l / running 3x a day approx |

Electric specifications

| | |
|----------------------|----------------|
| Input voltage: | AC 220-240 V |
| Frequency: | 50/60 Hz |
| Performance: | 3/4 HP (550 W) |
| Current consumption: | 2.25 A |
| Motor type: | Commutator DC |
| Engine speed: | 2700 rpm |
| Torque: | 1.8 Nm |
| Power cable: | CEE plug 7/7 |
| Power cord length: | 140 cm |

Dimensions, weight, packaging

| | |
|----------------------------------|--|
| Device weight: | 4,7 kg |
| Device dimensions: | 413x167x167 mm (h/w/d) |
| Packaging dimensions: | 475x230x230 mm (h/w/d) |
| Packing method: | Protective polybag, polystyrene cover, cardboard box |
| Width of the packaging: | 23 cm |
| Height of the packaging: | 47.5 cm |
| Depth of the packaging: | 23 cm |
| Weight including packaging (kg): | 5.6 |

Protective and security elements

| | |
|-------------------------------|--|
| Resettable thermal fuse: | Yes, reset via fuse button |
| Short circuit protection: | Yes |
| Interference filter: | Yes, it meets EMC-electromagnetic standards. compatibility |
| Electricity class protection: | I. (protective conductor) |

