

EcoMaster Samostatné pneutlačítko hranaté

Slouží k ovládání drtiče kuchyňského odpadu



EAN: 8596220003003

30,84 €

25,70 € excluding VAT



EAN: 8596220003027

34,92 €

29,10 € excluding VAT



EAN: 8596220000095

42,96 €

35,80 € excluding VAT

For simple, convenient, and at the same time safe operation of kitchen waste disposals. This option is the most commonly used as the disposal is turned on and off in conjunction with water, allowing the button to be placed in close proximity to the faucet.

Location: In the worktop or directly into the free areas of the sink.

Safety: The button meets all safety requirements. It is suitable for humid environments and can even be directly poured with water. In addition to controlling crushers, it is also used, for example, to activate jets in whirlpools and large hot tubs.

Function: The button does not directly give an electrical impulse, but by the pressure of compressed air through the hose, it switches the pneumatic mechanism inside the tire crusher, which operates the

electrical micro switch separated by a diaphragm. The button and the waste crusher are connected only by an air hose.

Note: Necessary for controlling the crusher unless another method of activation is chosen (e.g. toggle or wireless switch). The hose, if needed, must be ordered separately.

Components included in the package:

- The body of the switch with an air bladder.
- Selected button cover

Parameters

Basic parameters

| | |
|----------------------------------|--|
| Model: | Dull stainless steel brushed / Copper patina / Old brass |
| Use: | Air pressure switching - crushers, whirlpools, pools |
| Warranty: | 2 |
| Weight including packaging (kg): | 0.3 |
| Width of the packaging (cm): | 21 |
| Height of packaging (cm): | 7 |
| Depth of packaging (cm): | 30 |

Technical parameters

| | |
|---|---|
| Method of attachment / installation: | Downloading matrix |
| Button material: | Screwing, nut - plastic |
| Thread diameter.: | 32 mm |
| The diameter of the cover around the button.: | 47 x 47 mm |
| Thread length for fastening: | Possible length of engagement 54 mm - meaning possible thickness of the board |



EcoMaster pneumaticitko

Model izvedbi: matni nerjav, bronza, rdeča, starmosaz, mlatj zelena

