

Jet Dryer DUO 2v1

Nad automatickou baterií se nachází vyústění trysky vysoušeče.



EAN: 8596220010353

481,44 €

401,20 € bez DPH

The innovative design of the Jet Dryer DUO combines a jet dryer with an automatic faucet. You can conveniently wash and dry your hands in one place - directly at the sink. The Jet Dryer DUO is equipped with a HEPA filter. Both the faucet and the dryer operate without contact for maximum hygiene. Thanks to each sink having its own dryer, the operation in the toilets is smooth and without queues.

Welt Servis spol. s r.o. keeps products and spare parts in stock and provides both warranty and post-warranty [service](#).

Innovative design for easy use.

Hand washing and drying has never been easier. By placing your hands under the faucet, water will automatically flow at a pre-set temperature. Just above the automatic faucet is the outlet of the hand dryer nozzle. Activation is also contactless, simply insert your hands and move them as you would when washing. On the front part of the dryer arm, there is an illuminated ring. The ring pulsates with white light, indicating the dryer's function. It shines blue while in use.

Durable and compact

The battery body with a hairdryer in the shape of the letter F is made of high-quality brushed steel. The hairdryer unit is securely hidden under the sink, out of the reach of any potential vandals. Therefore, the hairdryer does not unnecessarily take up space.

HEPA filtration

The air passing through the dryer is purified by a HEPA filter with the ability to capture over 99.9% of particles the size of bacteria and viruses. In combination with completely contactless use, the Jet Dryer DUO dryer is therefore maximally hygienic.

Always dry and clean floor

Thanks to the fact that the hands can be dried directly in the sink, the floor of your bathrooms will not be splattered by visitors moving to the paper towel dispenser or hand dryer. In addition, you will no longer have to worry about emptying bins full of paper towels.

Automatic air heating

In case the temperature in the toilets is low, the Jet Dryer DUO will automatically turn on the air heating. The blown air can also be continuously heated, regardless of the surrounding temperature.

4 speed levels

With the Jet Dryer DUO, you can choose from four drying speeds. At the lower setting, the operation of the dryer is very quiet. At higher settings, the drying time is shorter. You can easily switch between speeds on the control panel on the dryer unit.

Always safe operation

The Jet Dryer DUO hand dryer is equipped not only with protection against short circuits and overloads, but also with an auto-stop function. In case of prolonged operation, it will automatically shut off. Drying is turned off after 45 seconds of continuous operation.

Adjustable water temperature

Each package of a hand dryer with a 2-in-1 faucet includes a mixing valve allowing you to adjust the water temperature to your liking. The Jet Dryer DUO can also be connected directly to cold water.

Simple assembly

Installation of the hand dryer in the Jet Dryer DUO faucet is possible without the need for major construction modifications. The unit can be easily placed under the sink. Another option is mounting it on a wall bracket.

Parts of the packaging:

- Assembly instructions
- Assembly suspension panel
- 5 x 25 mm self-tapping screw, 4 pieces.
- 5 mm anchor 4 pieces.

Parameters

Basic parameters

Model:	Jet Dryer DUO
Use:	Representative washrooms and bathrooms, busy operations, places limited by space.
Product TARIC code:	85163300
Warranty:	2 years

Technical parameters

Method of securing the unit:	Position under the sink / wall-mounted
Battery installation method:	To the sink drain.
Cover material of the unit:	White ABS plastic
Material of the battery body:	Stainless steel
Surface finish - color:	Brushed stainless steel
Noise - sound level:	75 dB
Controls:	Capacitive buttons
Status indication:	LED on the unit, backlit ring on the shoulder strap
Trigger System (Power On, Control):	Automatic-infrared sensor
Switching distance:	8-12 cm
Warm air:	YES - according to ambient temperature / permanently on
Change engine speed / air speed:	4 speed levels
Air flow:	up to 4 l/min at a pressure of 0.4 MPa
Air Speed:	90 m/s
Operating temperature:	0 °C / + 40 °C
Standard air filter:	Yes
HEPA filter:	Yes
HEPA filter class:	H13
Appropriate water temperature:	0-80 °C
Case material:	Stainless steel
Type:	In the battery

Electric specifications

Input voltage:	AC 220-240 V
Frequency:	50/60 Hz
Power input:	1350-1550 W
Heating element output:	650-750 W
Motor power:	700 W
Motor type:	Serial AC commutator
Current consumption:	6.1 A.
Standby mode:	<2 W
Power cable:	CEE plug 7/7
Power cord length:	130 mm

Protective and security elements

Protection against excessive use:	Yes
Overcurrent protection, overheating and short-circuit protection:	Yes
Electricity class protection:	II. (amplified insulation)
Degree of protection:	IP24

Dimensions, weight, packaging

Unit dimensions:	315x216x191 mm (w/h/d)
Battery body dimensions:	318.5x183 mm (w/h)

Packaging dimensions:	320x530x260 mm (w/h/d)
Unit weight:	5.7 kg
Weight including packaging (kg):	7.5 kg
Packing method:	Protective polybag, polystyrene cover, cardboard box
Width of the packaging (cm):	53
Height of packaging (cm):	32
Depth of packaging (cm):	26



